




NW
CREE XM-L NW
Cutter-XML20STE3-T6
XMLAWT-0-3C0-T60-0L-0001

CW
CREE XM-L CW
Cutter-XML20STR-U2
XMLAWT-0-2S0-U20-00-0001

RB
CREE XP-E RB
Cutter-XPE20STRROY-5
XPEROY-L1-D50-16-0-01
Min Flux of 500mw

B
CREE XP-E B
Cutter-XPE20STRBLU
XPEBLU-L1-0000-00201

UV
Prolight 3W UV LED Star
<http://www.led-bulbs.com/>

Red
Osram-660nm-3W-Red

Deep-Red 1-Up EndorStar

420nm UVR 1 BT 420nm

Профиль АВ0093 150x172x38мм

<http://www.chipdip.ru/product/ab0093-150x172x38mm.aspx>



XLamp XP-E LED Standard Order Codes - Royal Blue							
Color	Min. Radiant Flux (mW) @ 350 mA*		Dominant Wavelength (nm)				Order Code
			Min.		Max.		
	Group	Flux (mW)	Group	DWL (nm)	Group	DWL (nm)	
Royal Blue	14	350	D3	450	D5	465	XPEROY-L1-0000-00901
			D3	450	D4	460	XPEROY-L1-0000-00902
			D4	455	D5	465	XPEROY-L1-0000-00903
	15	425	D3	450	D5	465	XPEROY-L1-0000-00A01
			D3	450	D4	460	XPEROY-L1-0000-00A02
			D4	455	D5	465	XPEROY-L1-0000-00A03
	16	500	D3	450	D5	465	XPEROY-L1-0000-00B01
			D3	450	D4	460	XPEROY-L1-0000-00B02

XLamp XP-E LED Standard Order Codes - Color							
Color	Min. Luminous Flux (lm) @ 350 mA*		Dominant Wavelength (nm)				Order Code
			Min.		Max.		
	Group	Flux (lm)	Group	DWL (nm)	Group	DWL (nm)	
Blue	K2	30.6	B3	465	B6	485	XPEBLU-L1-0000-00Y01
			B3	465	B5	480	XPEBLU-L1-0000-00Y02
			B4	470	B5	480	XPEBLU-L1-0000-00Y05
	K3	35.2	B3	465	B6	485	XPEBLU-L1-0000-00Z01
			B3	465	B5	480	XPEBLU-L1-0000-00Z02
			B4	470	B5	480	XPEBLU-L1-0000-00Z05
	M2	39.8	B3	465	B6	485	XPEBLU-L1-0000-00201
			B3	465	B5	480	XPEBLU-L1-0000-00202
			B4	470	B5	480	XPEBLU-L1-0000-00205

Flux Characteristics at 700mA, $T_J = 25^{\circ}\text{C}$

Radiation Pattern	Color	Part Number		Radiometric Power (mW)	
		Emitter	Star	Minimum	Typical
Lambertian	UV	PG1C-3LLE	PG1C-3LLS	515	540

- ProLight maintains a tolerance of $\pm 10\%$ on flux and power measurements.
- Please do not drive at rated current more than 1 second without proper heat sink.


Electrical Characteristics at 700mA, $T_J = 25^{\circ}\text{C}$

Color	Forward Voltage V_F (V)			Thermal Resistance Junction to Slug ($^{\circ}\text{C}/\text{W}$)	Thermal Resistance Junction to Board ($^{\circ}\text{C}/\text{W}$)
	Min.	Typ.	Max.		
UV	2.85	3.5	4.1	8	13

Optical Characteristics at 700mA, $T_J = 25^{\circ}\text{C}$

Color	Peak Wavelength λ_P			Total included Angle (degrees) $\theta_{0.90V}$	Viewing Angle (degrees) $2\theta_{1/2}$
	Min.	Typ.	Max.		
UV	390 nm	400 nm	410 nm	160	140

- ProLight maintains a tolerance of $\pm 1\text{nm}$ for dominant wavelength measurements.









Deep-Red 1-Up EndorStar Features:

- 290mW @ 350mA
- 580mW @ 700mA
- 700mA - Max Drive Current
- 2.20Vf - Typ. Forward Voltage 350mA
- 2.40Vf - Forward Voltage 700mA
- 660nm - Typ. Wavelength
- 120° - Viewing Angle
- 135° C - Max Junction Temperature
- LXM3-PD01-0260 - Rebel Part#



660nm wavelength
 1000mA max
 2.15V @400mA

No secondary lenses are available for this product (yet)



TRC-040S105DS

40W - Constant Current - 0-10V Dimmable - Long Life Series - 487,000 Hour MTBF

Catalog #	Input Voltage	Output Voltage	Output Current	Output Power	Datasheet
		(revision date)			
TRC-040S035DS	90-305 VAC	38 - 114 VDC	350 mA	40W	Click Here (11/15/10)
TRC-040S045DS	90-305 VAC	30 - 89 VDC	450 mA	40W	Click Here (11/15/10)
TRC-040S070DS	90-305 VAC	18 - 54 VDC	700 mA	38W	Click Here (11/15/10)
TRC-040S105DS	90-305 VAC	12 - 36 VDC	1050 mA	38W	Click Here (11/15/10)
TRC-040S128DS	90-305 VAC	10 - 29 VDC	1280 mA	38W	Click Here (11/15/10)
TRC-040S140DS	90-305 VAC	10 - 25 VDC	1400 mA	36W	Click Here (11/15/10)
TRC-040S166DS	90-305 VAC	10 - 23 VDC	1660 mA	38W	Click Here (11/15/10)
TRC-040S222DS	90-305 VAC	6 - 16 VDC	2220 mA	36W	Click Here (11/15/10)
TRC-040S333DS	90-305 VAC	4 - 11 VDC	3330 mA	35W	Click Here (11/15/10)
Blue - Class 2 US/Canada		Green - Class 2 US only			



http://www.nanotuners.com/product_info.php?cPath=83&products_id=752

Features



- DC input voltage up to 32V
 - 1.0A, 1.4A, or 2.1A constant current output*
 - Extremely small form factor* (2.0"x1.2"x0.38")
 - 18 AWG wires for easy electrical connections
 - External analog/digital intensity control
 - External potentiometer intensity control (0-100%)
 - Continuous output short circuit protection
 - Continuous output open circuit protection
 - Input reverse polarity protection with Polarifet™ Technology
 - Pulse and strobe capable (dim input)
 - 0-10V Dimming compatible with many available controls
- ### Typical Applications

- Solar & Landscape Lighting
- Architectural Lighting
- Track Lighting
- Automotive & Marine Lighting
- Portable Lighting & Flashlights
- Point of Purchase Lighting
- Desk & Reading Lamps
- Signal & marker Lighting
- Flashing & Strobe Lighting
- Cabinet & Display Case Lighting
- Sign & Channel Letters
- Much More...

<http://www.cutter.com.au/categories.php?cat=Luxdrive+Drivers>

Table 1
Product Selection

Part Number	DC Input	Drive Current in (mA)	Control/ Dimming	Connection Type
A009-D-V-1000	10-32V	1000	0-10V	6 Wires
A009-D-V-1400	10-32V	1400	0-10V	6 Wires
A009-D-V-2100	10-32V	2100	0-10V	6 Wires